

Model: ULTA-50~300

Ultrasonic Heat Meter



Main Technical Data:

Diameter (mm)	Qn (m³/h)	Qmin (m³/h)	Qmax (m³/h)	Length (mm)
DN50	15	0.6	30	200
DN65	25	1	50	200
DN80	40	1.6	80	225
DN100	60	2.4	120	250
DN125	100	4	200	250
DN150	150	6	300	300
DN200	250	10	500	350
DN250	400	16	800	450
DN300	600	24	1200	500
Range ratio	R25			
Measurement Accuracy	EN1434、CJ128-2007 Class2			
Connection	Flange			
Pressure Loss	≦ 20KPa			
Pressure Level	≦ 1.6MPa			
Temperature sensor	3 m standard two lines PT1000 Temperature Sensor (cable length could be changed)			
Data Storage	Continuous store of 38 months record			
Power-off Protection	After power-off, meter could save all the record of before flow rate and the corresponding time, after power back, it recovery measure function automatically, and ensure the time continuation			
Communication mode	Wired: Mbus, Modbus, RS485, Pulse Output Wireless: LoRaWAN			
Power Supply	ER18505 Lithium battery (waterproof)			
Protection Class	IP68			
Environmental Class	Class B			
Temperature Range	(4~95) °C			
Temperature Difference	(3~70)K			
Installation Way	Inflow or Return flow installation (Default is Inflow installation, for return flow need to indicate when ordering)			
Permanence	Service cycle ≧ 6 years			
Display	LCD display			
Anti-magnetic Disturbance	When the intensity of magnetic field interference is not more than 100 ka/m, should not affect water meter measurement and remote transmission characteristics			